



Tabulka specifikací

| KAGW 2 Závěsná souprava | Označení | Nosnost 0°-45° [kg] | Nosnost 45°-60° [kg] | Pro řetěz- Ø | vhodné pro jednoduché háky dle. DIN 15401 | vhodné pro dvojitě háky dle. DIN 15402 |
|---|------------------------|---------------------------|----------------------------|--------------------|---|--|
|  | KAGW 2-6 ¹⁾ | 2.000 | 1.400 | 6 | 2,5 | 4 |
| | KAGW 2-7 | 2.650 | 1.900 | 7 | 2,5 | 4 |
| | KAGW 2-8 | 3.550 | 2.500 | 8 | 5 | 6 |
| | KAGW 2-10 | 5.600 | 4.000 | 10 | 6 | 8 |
| | KAGW 2-13 | 9.500 | 6.700 | 13 | 8 | 10 |
| | KAGW 2-16 | 14.000 | 10.000 | 16 | 10 | 12 |
| | KAGW 2-19/20 | 20.000 | 14.000 | 19 | 16 | 20 |
| | KAGW 2-22 | 26.500 | 19.000 | 22 | 25 | 32 |

| KAGW 2 Závěsná souprava | Označení | e [mm] | d [mm] | t [mm] | w [mm] | Hmotnost [kg/pc.] |
|--|------------------------|-----------|-----------|-----------|-----------|----------------------|
|  | KAGW 2-6 ¹⁾ | 141 | 13 | 110 | 60 | 0,59 |
| | KAGW 2-7 | 153 | 16 | 110 | 60 | 0,97 |
| | KAGW 2-8 | 178 | 19 | 135 | 75 | 1,38 |
| | KAGW 2-10 | 211 | 23 | 160 | 90 | 2,40 |
| | KAGW 2-13 | 243 | 27 | 180 | 100 | 4,13 |
| | KAGW 2-16 | 274 | 33 | 200 | 110 | 6,97 |
| | KAGW 2-19/20 | 354 | 36 | 260 | 140 | 11,75 |
| | KAGW 2-22 | 442 | 45 | 340 | 180 | 21,51 |
| ¹⁾ Může být použito pro řetěz průměru 5 mm, ale nosnost celého závěsu se sníží. | | | | | | |